



## QDF-CB

### Street cabinets

These street cabinets comprise a body and a pedestal. They are made of heavy-duty polymer with a mottled, UV-resistant paint finish.

Three sizes are available to accommodate from 800 to 1800 pairs. They are supplied ready-installed with 60 mm high mounting brackets (40 mm storage space), which are mounted on a stainless steel frame in 4 columns. Jumper routing guides are also provided. Magazines need to be ordered separately.

In the base of the cabinet itself are ten cable entry/exit ports to guide cable into or from the pedestal. 8 talk pairs are also provided, together with a shielding connection and an earthing point.

The roof of the cabinet contains aeration holes to minimise internal condensation.

The cabinet door is reinforced with an inner plate which features two oval fixtures to accommodate test cords, and one empty reel for jumper wire storage.

The door is fitted with a neoprene seal to give an IP rating of 43.

It has three fixed opening positions governed by a metal rod and is fitted with a lock operated by a triangular key. The mechanism is also adaptable to accept customer locks if required, and can also be padlocked.

The pedestal has a removable front door to facilitate cable installation into the cabinet. It is only accessible when the main front door is open.

## Ordering Information and Dimensions

Description (H x W x D mm)	Outside Dimensions	PCN Number
QDF-CB-0800-T	750 x 750 x 300	168177-000
QDF-CB-1000-T	750 x 750 x 300	024364-000
QDF-CB-1200-T	1000 x 750 x 300	335580-000
QDF-CB-1400-T	1000 x 750 x 300	129912-000
QDF-CB-1600-T	1250 x 750 x 300	131272-000
QDF-CB-1800-T	1250 x 750 x 300	559634-000

Pedestal dimensions: 400 x 750 x 300 mm.

The same pedestal is used for all three cabinet sizes.

## Accessories

With each cabinet, the following items are supplied

- one triangular key (polycarbonate)
- kits containing one magazine designation cover (grey) , one designation cover label and 1 tie wrap. 1 kit per 100 pairs
- a 2 m long test and break cord: QDF-4A1-2.

The following items are not supplied and will need to be ordered separately if required

Description	Part Number	PCN Number	Standard Packaging
QDF-E magazines	QDF-E1P	701381-000	10 per box
2 m monitor cord	QDF-2T1-2	054326-000	1 piece

## Materials

Cabinets are manufactured from fibre-glass reinforced polyester, UL94 V0 flammability rating.

The frames and mounting brackets are stainless steel.



Tyco Electronics, TE logo and QDF are trademarks

The information given herein, including drawings, illustrations and schematics which are intended for illustration purposes only, is believed to be reliable. However, Tyco Electronics makes no warranties as to its accuracy or completeness and disclaims any liability in connection with its use. Tyco Electronics' obligations shall only be as set forth in Tyco Electronics' Standard Terms and Conditions of Sale for this product and in no case will Tyco Electronics be liable for any incidental, indirect or consequential damages arising out of the sale, resale, use or misuse of the product. Users of Tyco Electronics products should make their own evaluation to determine the suitability of each such product for the specific application.

Tyco Electronics Raychem NV  
Diestsesteenweg 692  
3010 Kessel-Lo, Belgium  
Tel 32-16 351 011 (USA)1-919-557-8900  
Fax 32-16 351 697 (USA)1-919-557-8498  
www.tycoelectronics.com  
www.telecomosp.com  
TC 629/M/DS/1 03/01

Tyco Electronics Raychem, S.A.  
Polígono industrial Mediterráneo  
C/. La Fila, parcela 1  
46550 Albuixech-Valencia, España  
Tel 34-96-141 70 72  
Fax 34-96-141 74 15